



**NOTES:**

1. ALL MATERIALS TO BE ALUMINUM 6061-T6 ALLOY.
2. WELD ALL INTERSECTIONS.
3. FASTEN TO CONCRETE STRUCTURE WITH 3/8 in. x 3 in. STAINLESS STEEL CONCRETE WEDGE ANCHORS AT 18 in. MAX. SPACING. MINIMUM OF (4).
4. DEPTH TO O.D. OF RACK. IF THE CONCRETE WEIR EXTENDS TO THE TOP OF THE STRUCTURE, THE DEPTH OF THE TOP BARS WILL EXTEND TO MEET TOP GRATING OR FRAME OF STRUCTURE SO THERE IS NO GAP.
5. OVERALL RACK WIDTH = (W) + 4 INCHES
6. OVERALL RACK HEIGHT = (H) + BAR DIAMETER + 2 INCHES
7. OPTIONAL - 10g STAINLESS STEEL WIRE MESH WITH 1 in. GRID TO COVER RACK.

TRASH RACK INFORMATION	
RACK WIDTH I.D. (W)	
RACK HEIGHT I.D. (H)	
RACK DEPTH O.D. (D)	
BAR DIAMETER (1/2" OR 3/4")	
BAR CENTERLINE SPACING	
STRUCTURE OPENING W	
STRUCTURE OPENING H	
WEIR EXTENDS TO TOP?	
FASTENERS (QTY)	
WIRE MESH?	
NOTES:	

This CAD file and drawing is the property of Effluent Design & Fabrication, LLC. It is intended for the named recipient. Unauthorized reproduction, disclosure, or distribution is strictly prohibited.

 <b>Effluent</b> Design & Fabrication, LLC <a href="http://www.effluentdesignfab.com">www.effluentdesignfab.com</a>	6 William Martin Way Flemington, NJ 08822
	Phone: 908.458.9220 FAX: 908.458.9930
PROJECT: ALUMINUM BOXED SERIES AB RACK	FILE #:
	DATE:
	SCALE:
	DRAWN BY: